ORION+ CONNECTOR INSTALLATION/ COMMUNICATION/ UPGRADE

SOFTWARE MANUAL

1. PC Software Installation

The ORION-PLUS configuration application is based in the Google Chrome framework, so make sure that the Google Chrome is installed in your computer before starting the installation process.

Installation procedure:

- 1. Download the Zip file to your computer.
- 2. Locate the Zip file on your computer and extract it to an empty folder.
- 3. Go to chrome://extension/ or navigate through the menus and check the box for Developer mode in the top right.

		🕸 🞯 🖸 🖓 Paused 🦢 👔		
		New tab Ctrl=T New window Ctrl=N New incognito window Ctrl=Shift=N		
		History Counceds Ctri+) Bookmarks	Details Remove	-
		Zoom - 100% - 23		
	1	Print Ctrl+P Cast Find Ctrl+F		
Save page a	6 Ctrl+S	More tools		
Create shore	tcut	Edit Cut Copy Paste		
Clear brows Extensions Task manag	ng data Ctri-Shift-Dei er Shift-Esc	Settings Help		
Developer t	ools Ctrl+Shift+I	Exit		



4. Click the Load unpacked button and select the folder with your extracted files to install the app.

E Extensions				Q. Developer mode
Load unpacked	Pack extension 1	lpdate		
Ortats	Remove		Details Ramove	
Chrome App	•			

5. Click 'app' and the application should now show up in the Google Chrome application launcher.



2. Configuration Upload/Download

- 1. Connect USB cable between panel and PC.
- 2. Select panel menu 8-4-2.
- 3. Open software and select Send Configuration or Get Configuration in Comms tab.

UNION+ C		puons + Commis+
General	Zones	 Get Configuration Send Configuration
Miscella	neous	Send Firmware





3. Firmware Upgrade

1. Open the ORION+ CONNECTOR, go to file and click 'Open'.

ORION+ CONNECT	OR 🔓 File 🕶	Options -	₽ Comms +
General Zones	🔝 New 🎘 Open		
Miscellaneous	🖪 Save		
	C+ Exit		

2. Select the firmware file (*.gfc). Now it should show the firmware information on the screen.

ORION+	CONNECTOR	🔓 File 🕶	Options -	₽ Comms •
Firmware				
Firmware	configuration (image	ge version 1, f	or Orion Plus Main	Panel 2.00, build 000)

- Connect the USB cable between the computer and the panel.
 Note: Drivers should not be necessary because the panel uses the USB 'hid' profile.
- 4. On the panel, go to the function 8-4-2 "Upload/Download Link to PC" and press 'OK' to enter the function. Once inside the function press the 'right key' to set the panel ready for the transfer. Note: After pressing the 'right key' the transfer should start within 20 secs, if not the panel will automatically reboot.
- **5.** After pressing the right key, a blue arrow should show up in the up-right corner of the application, meaning that it detected the control panel. Press the arrow to start the upgrade. The upgrade should take only a few seconds.

	×
About	
\odot	

GLOBAL FIRE EQUIPMENT S.A.

Sítio dos Barrabés, Armazém Nave Y, Caixa Postal 908-Z, 8150-016 São Brás de Alportel - PORTUGAL Tel: +351 289 896 560 • Sales: sales@globalfire.pt • Technical Support: techs@globalfire.pt • www.globalfire.pt